

DOCCT0000059-02

DIECI

DIECI



**DIECI RANGE
CONSTRUCTION**

Dieci S.r.l.
Via E. Majorana, 2-4
42027 Montecchio Emilia (RE) ITALY
info@dieci.com

dieci.com



**DIECI RANGE
CONSTRUCTION**



dieci.com



TELESCOPIC HANDLERS




Model	Manufacturer	Power (kW)	Capacity (kg)	Height (m)	Width (mm)
APOLLO 26.6	Kubota	55 kW (74 HP)	2600 kg (5732 lb)	5.68 m (18.6 ft)	4125 mm (162.4 in)
DEDALLUS 28.7 - GD	Kubota	79.5 kW (107 HP)	2900 kg (6393 lb)	6.35 m (20.8 ft)	4720 mm (185.8 in)
DEDALLUS 30.7 - GD	Kubota	79.5 kW (107 HP)	3000 kg (6614 lb)	6.35 m (20.8 ft)	4720 mm (185.8 in)
DEDALLUS 28.9 - GD	Kubota	79.5 kW (107 HP)	4000 kg (8818 lb)	8.65 m (28.4 ft)	4755 mm (187.2 in)
DEDALLUS 30.9 - GD	Kubota	79.5 kW (107 HP)	4000 kg (8818 lb)	8.65 m (28.4 ft)	4755 mm (187.2 in)
ZEUS 40.7 - GD	Kubota	55.4 kW (74 HP)	3000 kg (6614 lb)	7.2 m (23.6 ft)	4971 mm (195.7 in)
ZEUS 38.8 - GD	Kubota	55.4 kW (74 HP)	4000 kg (8818 lb)	7.6 m (24.9 ft)	5435 mm (214 in)
ZEUS 38.10 - GD	Kubota	55.4 kW (74 HP)	4000 kg (8818 lb)	9.6 m (31.5 ft)	4995 mm (196.7 in)
ZEUS 35.11 - GD	Kubota	55.4 kW (74 HP)	3000 kg (6614 lb)	10.6 m (34.8 ft)	5270 mm (207.5 in)
ZEUS 40.13 - GD	Kubota	55.4 kW (74 HP)	4000 kg (8818 lb)	12.5 m (41 ft)	5970 mm (235 in)
ICARUS 40.14 - GD	Kubota	85.1 kW (114 HP)	3800 kg (8378 lb)	13.40 m (44 ft)	6200 mm (244.1 in)
ICARUS 40.17 - GD	Kubota	85.1 kW (114 HP)	4000 kg (8818 lb)	16.40 m (53.8 ft)	6250 mm (246.1 in)
ICARUS 50.18 - GD	Kubota	85.1 kW (114 HP)	5000 kg (11023 lb)	17.80 m (58.4 ft)	6900 mm (271.7 in)
SAMSON 50.8 VS EVO2 - GD	FPT	103 kW (138 HP)	4000 kg (8818 lb)	7.70 m (25.3 ft)	5023 mm (197.8 in)
SAMSON 65.8 VS EVO2 - GD	FPT	103 kW (138 HP)	6500 kg (14330 lb)	7.70 m (25.3 ft)	5023 mm (197.8 in)
SAMSON 60.9 VS EVO2 - GD	FPT	103 kW (138 HP)	6000 kg (13228 lb)	8.60 m (28.2 ft)	5373 mm (211.5 in)
SAMSON 75.10	FPT	103 kW (138 HP)	7500 kg (16535 lb)	9.65 m (31.7 ft)	5910 mm (232.7 in)
PIVOT40	Kubota	36.5 kW (49 HP)	1800 kg (3968 lb)	4.00 m (13.1 ft)	5035 mm (198.2 in)
PIVOT50	Kubota	54.6 kW (73 HP)	2250 kg (4960 lb)	4.70 m (15.4 ft)	5400 mm (212.6 in)
PIVOT60	Kubota	54.6 kW (73 HP)	3000 kg (6614 lb)	4.70 m (15.4 ft)	5400 mm (212.6 in)
PIVOT70	Kubota	83.5 kW (112 HP)	4000 kg (8818 lb)	5.00 m (16.4 ft)	5520 mm (217.3 in)
PIVOT80	FPT	96 kW (129 HP)	4100 kg (9039 lb)	5.20 m (17.1 ft)	5895 mm (232.1 in)
PIVOT90	FPT	103 kW (138 HP)	4100 kg (9039 lb)	5.7 m (18.7 ft)	6440 mm (253.5 in)

TRUCK MIXER



Model	Manufacturer	Power (kW)	Capacity (L)	Height (m)	Width (mm)
ABN 2400	Lombardini	36.6 kW (49 HP)	270 L (71.3 gal)	1.7 m (60 ft)	105x18"
ABN 2400T	Lombardini	36.6 kW (49 HP)	-	1.7 m (60 ft)	105x18"
AB L 3500	Perkins	85.9 kW (115 HP)	500 L (132.09 gal)	2.5 m (88 ft)	12.5x18"
AB L 3500T	Perkins	85.9 kW (115 HP)	500 L (132.09 gal)	2.5 m (88 ft)	12.5x18"
AB L 3500 CCS	Perkins	85.9 kW (115 HP)	500 L (132.09 gal)	2.5 m (88 ft)	12.5x18"
AB L 4700	Perkins	85.9 kW (115 HP)	600 L (158.5 gal)	3.5 m (124 ft)	405/70x20"
AB L 4700 T	Perkins	85.9 kW (115 HP)	-	3.5 m (124 ft)	405/70x20"
AB L 4700 CCS	Perkins	85.9 kW (115 HP)	600 L (158.5 gal)	3.5 m (124 ft)	405/70x20"
AB F 7000	Perkins	100 kW (134 HP)	600 L (158.5 gal)	5.0 m (177 ft)	405/70R24"
AB F 7000 T	Perkins	100 kW (134 HP)	-	5.0 m (177 ft)	405/70R24"
AB F 7000 CCS	Perkins	100 kW (134 HP)	600 L (158.5 gal)	5.0 m (177 ft)	405/70R24"

DUMPER



Model	Manufacturer	Power (kW)	Capacity (m³)	Height (m)	Width (mm)
DUMPER 1000 F	Lombardini	15 kW (20 HP)	1.0 m³ (35 ft³)	1.2 m (42 ft)	7,5x16"
DUMPER 1000 T	Lombardini	15 kW (20 HP)	1.0 m³ (35 ft³)	1.2 m (42 ft)	7,5x16"
DUMPER 1000 PA	Lombardini	15 kW (20 HP)	1.0 m³ (35 ft³)	1.2 m (42 ft)	7,5x16"
DUMPER 8000	FPT	125 kW (168 HP)	8.00 m³ (283 ft³)	8.50 m (300 ft)	12.00 - 24"

ROTATIVE HANDLERS



Model	Manufacturer	Power (kW)	Capacity (kg)	Height (m)	Width (mm)
PEGASUS 38.16 - 400"	Kubota	73.4 kW (98 HP)	2600 kg (5732 lb)	15.70 m (51.5 ft)	6740 mm (265.4 in)
PEGASUS 40.18 - 400"	Kubota	73.4 kW (98 HP)	2600 kg (5732 lb)	18.00 m (59.1 ft)	6630 mm (261 in)
PEGASUS 40.25	FPT	96 kW (129 HP)	4000 kg (8818 lb)	18.70 m (61.4 ft)	8000 mm (315 in)
PEGASUS 50.19	FPT	96 kW (129 HP)	5000 kg (11023 lb)	15.70 m (51.5 ft)	6740 mm (265.4 in)
PEGASUS 50.21	FPT	96 kW (129 HP)	5000 kg (11023 lb)	20.50 m (67.3 ft)	7150 mm (281.5 in)
PEGASUS 60.16	FPT	96 kW (129 HP)	6000 kg (13228 lb)	15.70 m (51.5 ft)	6720 mm (264.6 in)
PEGASUS 45.30	FPT	125 kW (168 HP)	4000 kg (8818 lb)	25.7 m (84.3 ft)	8409 mm (330.7 in)
PEGASUS 50.26	FPT	125 kW (168 HP)	5000 kg (11023 lb)	25.7 m (84.3 ft)	8409 mm (331.1 in)

HEAVY DUTY



Model	Manufacturer	Power (kW)	Capacity (kg)	Height (m)	Width (mm)
HERCULES 100.10	FPT	125 kW (168 HP)	3500 kg (7716 lb)	9.50 m (31.2 ft)	6050 mm (238.2 in)
HERCULES 120.10	FPT	125 kW (168 HP)	4500 kg (9921 lb)	9.50 m (31.2 ft)	6050 mm (238.2 in)
HERCULES 190.10	FPT	125 kW (168 HP)	19000 kg (41888 lb)	10.20 m (33.5 ft)	6800 mm (267.7 in)
HERCULES 210.10	FPT	125 kW (168 HP)	21000 kg (46297 lb)	10.20 m (33.5 ft)	6800 mm (267.7 in)
HERCULES 230.10	FPT	125 kW (168 HP)	23000 kg (50706 lb)	10.15 m (33.3 ft)	6800 mm (267.7 in)

* riferita a ruote con diametro massimo ammesso - * referred to wheels having the maximum allowable diameter - * en référence à des roues ayant un diamètre maximum admis * referida a ruedas con un diámetro máximo admitido - * in Bezug auf Reifen mit maximal zulässigem Durchmesser - * Odnosi się do kół o maksymalnie dopuszczalnej średnicy - * Referente às rodas com diâmetro máximo admitido - * относится к колесам с максимально допустимым диаметром